

## Personal Health Gateway – 750

## Low-Cost POTS Connectivity

- ❖ Open standards connectivity for both data collection and uploading. Supports all Continua and Bluetooth Low Energy Med devices. Uploads to FHIR servers, or HL7 V.2 gateways
- ❖ Provides Wi-Fi and Dial-up (POTS) Connectivity for remote or limited bandwidth areas
- ❖ Has a Display and Sound for Auditory and Visual Cues for collecting measurements
- ❖ Meets clinical requirements for patient identity, timestamping and measurement representation
- ❖ Transparent to user – no user facing interface to learn
- ❖ Diagnostic tooling to resolve common user issues, including remote Bluetooth pairing
- ❖ Security framework built on dual certificate SSL, BTLE encryption, OAuth, and SAML
- ❖ Operates without requiring Personal Health Information nor storing any data in transit
- ❖ Support for enterprise scale provisioning
- ❖ Available off the shelf, as a white-labeled product or part of a turnkey Health@Home program



The first standards-based, multi-user remote hardware hub addressing patient identity, correctness of time and measurement representation for clinical-grade remote health monitoring.

Display and speaker allow for positive confirmation of results taken and sent.

Display can be customized to show specific connectivity results or statuses.

WiFi and Dial-up Connectivity

Easy-to-provision and pre-pair devices

## Regulatory Approval

The Health@Home PHGs have achieved the following regulatory approval:

- United States FCC (Contains FCC ID: 2ABCB-RP132)
- Canada IC (Contains IC: 20953-RP132)
- European Union: CE Mark
- Japan Radio Law Conformity Mark: 205-160251
- FDA - Classification is as a Medical Device Data System which is not classified as a Medical Device
- European Union - The PHG750 is not considered to be a medical device (93/42/EEC)



The label displays the serial number, model, and the sticker address used in configuring the hub (can also be scanned using the bar code)

US FCC ID, Canada IC ID, CE mark, Japan Radio compliance

---

---

## Power Supply

The typical Health@Home PHG750 operates with a power draw of about 100 - 130mA while plugged into a standard electric outlet. Peak power consumption is about 290 mA.

When being used with a USB battery source, LNI recommends using a power supply that can provide 2.5 Amps of USB power.



The PHG750 is powered using the micro USB connector (left). The PHG750 also provides an audio port for headphones and a mini-HDMI port

---

---

## Network Connectivity

Supported network connectivity options include:

- IEEE 802.11 with support for 2.4 GHZ
- Standard Telephony dial-up connection via an RJ11 jack

---

---

## Supported Devices

The PHG750 supports open standards. This includes all devices that use the IEEE 11073-20601 protocol, and devices supporting the Bluetooth and Bluetooth Low Energy Medical Device profiles.

Additionally, a collection of non-standard devices is supported. See <https://www.lnihealth.com/device-category> for the current list.

LNI offers additional device inclusion for customers on an as-identified basis. LNI's experienced team can assist in incorporating new custom sensor devices into the Health@Home ecosystem.



## Supported Transports

11073 Device Specializations (USB PHDC and Bluetooth HDP)	<p>All Continua Defined Device Specializations are supported. The following commonly used specializations have been tested against products in the marketplace:</p> <ul style="list-style-type: none"><li>• Blood Pressure Cuff</li><li>• Blood Glucose</li><li>• Weight Scale, including Body composition analyzer</li><li>• Pulse Oximeter</li><li>• Activity Monitor</li></ul>
BTLE Medical Device Profiles (Bluetooth LE)	<p>All Continua defined BTLE Personal Health Devices, which includes:</p> <ul style="list-style-type: none"><li>• Heart Rate</li><li>• Blood Glucose</li><li>• Blood Pressure</li><li>• Blood Oxygen (pulse ox)</li><li>• Thermometer</li><li>• Weight Scale</li></ul>

## Bluetooth Capabilities

- White listing
- Auto-pair
- Ability to connect with non-pairing Bluetooth random address devices
- Bluetooth Encryption
- Additional advanced options for managing specific Bluetooth compatibility issues

---

## Storage Medium

The PHG750 application uses a 16 GB class 10 Micro SD card for persistent storage. No external access is available to the end user. All updates can be performed remotely. Updating can be scheduled and completed at controlled release times.

*No User data is stored on device*

---

## Single Enterprise System

All hubs run the same HubOS allowing for a common implementation experience and same device support. Exchange provides a consistent Management interface across all hub types. This allows for common profiles and simplified management tools.

---

---

## Management Interface

Management of the PHG750 can be accomplished via Health@Home Exchange or by connecting to the local http server on the device.

Patient Identity	When multiple patients are using the PHG750 to upload health data, patient identity can be established by using Health@Home Exchange to set a default user to be assigned to all measurements
Provisioning and Operational Management	The PHG750 can be fully provisioned remotely, allowing “plug in and go” deployments. Additional real-time white-listings are available either via the Health@Home Exchange portal or service API
Diagnostic and Logging	The following log capability exists: <ul style="list-style-type: none"><li>• Audit log for all received, sent, and dropped observations</li><li>• Connectivity management, including cellular signal integrity</li><li>• Bluetooth device pairing and transfers</li><li>• Changes in configuration</li></ul>
Remote Provisioning	The PHG750 can be remotely provisioned such that the device simply needs to be plugged in when on-premises in order to be ready to take measurement.
Companion Application	Android and iOS applications allow the PHG750 to be attached to a WiFi network during initial deployment. These applications are simple enough to be used by nonprofessional care provider

## Capabilities

- Localization capabilities (Language - English, German, Wi-Fi Regulatory domain, time zone)
- Selectable value for MQTT keep alive (manages cellular bandwidth utilized for management)
- Ability to set contact and location information for PHG750 (manual)
- Ability to setup Emergency account to allow login when password is lost
- Support for RADIUS server with enterprise WiFi configurations
- Use UAC segment in PCD-01 messages to pass method of patient identification
- Configurable setting to enable deleting of stored observations
- Configurable setting to support devices that provide streamed or spot observations (Pulse Oximeter)
- Remote Management of Dial-up connectivity
- Defined delay for collecting measurements and dialing out once

---

---

## Measurement Upload Capabilities

Feature	Description of Feature	Notes
Exchange Support	<ul style="list-style-type: none"><li>• Uploads observations to Exchange</li><li>• Implements H.812.3 Capability Exchange – allowing for automated discovery and configuration of services</li><li>• Automated first boot – Allows PHG750 to startup without user action in home deployment</li><li>• Remote operational control in real time</li><li>• Software updating. Remote pairing, cellular status, device battery management</li></ul>	
Security Framework	<ul style="list-style-type: none"><li>• Transport Security for IP - TLS 1.1</li><li>• Authorization - OAuth 2.0 (H.812.5, Capability Exchange), SAML 2.0 (H.812.1), Two way TLS authorization (boot server)</li><li>• Bluetooth - Encryption and pairing required</li></ul>	
Measurement Upload	<ul style="list-style-type: none"><li>• Upload of observation using Continua H.812.1 SOAP upload (IHE PCD-01/HL7 v2.6 payload with SOAP header and body)</li><li>• Upload of observation using Continua H.812.5 (will work with both FHIR observation server, and FHIR observation reporting server)</li></ul>	

---

---

## An Experienced Partner in Connected Health

Lamprey Networks (LNI) is a leading provider of interoperability solutions for remote monitoring in healthcare and life sciences. We are passionate devotees of technical standards that facilitate end-to-end, plug-and-play solutions, and designing solutions that are easy to use, manage and customize.

In addition to its solutions, LNI is widely recognized for its engineering services related to interoperability and compliance for emerging technical standards. We have been providing industry solutions to large commercial customers since 2008.

### Remote Monitoring, Your Way - Turnkey, by Component or White Label

# Health@Home

Health@Home is LNI's flagship remote monitoring solution for next-generation connected health in long term care and rehabilitation, chronic disease management, remote physician visits and clinical research. Designed for usability, scalability and customization, Health@Home is the most comprehensive standards-based, end-to-end, plug-and-play remote monitoring suite in the market today—comprising hardware and software hubs, cloud solution, servers and remote monitoring management services. Reflecting LNI's commitment to 'right size' partnership, Health@Home is available as a complete turnkey solution; or, its components can be purchased by integrators and developers to supplement existing resources, capabilities or equipment. This enables LNI's partners to invest incrementally in open, standards-based plug-and-play remote health monitoring. Health@Home offers attractive economies of scale along with reduced OS complexities and can be white labeled for seamless integration into a branded remote monitoring program or solution.

# LNI Health

We're dedicated to 'right size' partnerships in next generation connected health. For more information about LNI's turnkey Health@Home Remote Monitoring Solution, customized or white label orders, or LNI's specialized Engineering Services, please contact:

Chuck Parker

781-724-8872

[chuckparker@lnihealth.com](mailto:chuckparker@lnihealth.com)